

Package: directadjusting (via r-universe)

June 4, 2026

Type Package

Title Directly Adjusted Estimates

Version 0.6.1

Description Compute estimates and confidence intervals of weighted averages quickly and easily. Weighted averages are computed using data.table for speed. Confidence intervals are approximated using the delta method with either using known formulae or via algorithmic or numerical derivation.

License MIT + file LICENSE

URL <https://github.com/FinnishCancerRegistry/directadjusting/>

BugReports <https://github.com/FinnishCancerRegistry/directadjusting/issues>

Depends R (>= 2.10)

Imports data.table, stats

Encoding UTF-8

Language en-GB

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Repository <https://finnishcancerregistry.r-universe.dev>

Date/Publication 2026-05-25 10:36:20 UTC

RemoteUrl <https://github.com/finnishcancerregistry/directadjusting>

RemoteRef HEAD

RemoteSha 5fa638089f5f34e1e565914342c7a5ecc43edc35

Contents

confidence_intervals	2
directly_adjusted_estimates	4

Index	10
--------------	-----------

confidence_intervals *Confidence Intervals*

Description

Functions to compute confidence intervals.

Usage

```
delta_method_confidence_intervals(
  statistics,
  variances,
  conf_lvl = 0.95,
  conf_method = "identity"
)
```

Arguments

statistics	[numeric] (no default)
	Statistics for which to calculate confidence intervals.
variances	[numeric] (no default)
	Variance estimates of statistics used to compute confidence intervals.
conf_lvl	[numeric] (default 0.95)
	Confidence level of confidence intervals in]0, 1[.
conf_method	[character, call, list] (default "identity")
	Delta method transformation to be applied.
	<ul style="list-style-type: none"> character: Use one of the pre-defined transformations. Table of options with the corresponding expressions:

name	g	g_inv	g_gradient
identity	theta	g	1
log	log(theta)	exp(g)	1/theta
log-log	log(-log(theta))	exp(-exp(g))	1/(theta * log(theta))
logit	log(theta) - log(1 - theta)	1/(1 + exp(-g))	1/(theta - theta^2)

- call: A quoted R expression which produces the lower / upper limit when evaluated. E.g. `quote(theta * exp(z * theta_standard_error / theta))`.
- list: Contains both the transformation and its inverse. E.g. `list(g = quote(log(theta)), g_inv = quote(exp(g)))`.

Value

directadjusting::delta_method_confidence_intervals

Returns a data.table with columns c("statistic", "variance", "ci_lo", "ci_hi").

Functions

directadjusting::delta_method_confidence_intervals

directadjusting::delta_method_confidence_intervals can be used to compute confidence intervals using the delta method. The following steps are performed:

- Compute confidence intervals based on `conf_method`, `statistics`, `variances`, and `conf_lvl`.
 - If `conf_method` is a string, a pre-defined set of mathematical expressions are used to compute the confidence intervals.
 - If `conf_method` is a call, it is evaluated with the variables `theta`, `theta_variance`, `theta_standard_error`, and `z`. This is done once for the lower and once for the upper bound of the confidence interval, so for the lower bound and `conf_level = 0.95` we use `z = stats::qnorm(p = (1 - conf_lvl) / 2)`.
 - If `conf_method` is a list, it must contain elements `g` and `g_inv`, e.g. `list(g = quote(log(theta)), g_inv = quote(exp(g)))`.
 - * `g` is passed to `[stats::deriv]`. If that fails, a numerical derivative is computed.
 - * With the derivative known the variance after the transformation is `variance * g_gradient ^ 2`.
 - * With the transformed variance known the transform confidence interval is calculated simply via `g(theta) + g_standard_error * z`.
 - * These transformation-scale confidence intervals are then converted back to the original scale using `g_inv`.
- Collect a `data.table` with the confidence intervals and with also the columns `statistics = statistics` and `variance = variances`.
- Add attribute named `ci_meta` to the `data.table`. This attribute is a list which contains elements `conf_lvl` and `conf_method`.
- Return `data.table` with columns `c("statistic", "variance", "ci_lo", "ci_hi")`.

Examples

```
# directadjusting::delta_method_confidence_intervals
dt_1 <- directadjusting::delta_method_confidence_intervals(
  statistics = 0.9,
  variances = 0.1,
  conf_lvl = 0.95,
  conf_method = "log"
)

# you can also supply your own math for computing the confidence intervals
dt_2 <- directadjusting::delta_method_confidence_intervals(
  statistics = 0.9,
  variances = 0.1,
  conf_lvl = 0.95,
  conf_method = quote(theta * exp(z * theta_standard_error / theta))
)

dt_3 <- directadjusting::delta_method_confidence_intervals(
  statistics = 0.9,
  variances = 0.1,
```

```

    conf_lvl1 = 0.95,
    conf_method = list(
      g = quote(log(theta)),
      g_inv = quote(exp(g))
    )
  )

dt_4 <- directadjusting::delta_method_confidence_intervals(
  statistics = 0.9,
  variances = 0.1,
  conf_lvl1 = 0.95,
  conf_method = list(
    g = quote(stats::qnorm(theta)),
    g_inv = quote(stats::pnorm(g))
  )
)
stopifnot(
  all.equal(dt_1, dt_2, check.attributes = FALSE),
  all.equal(dt_1, dt_3, check.attributes = FALSE)
)

```

directly_adjusted_estimates

Directly Adjusted Estimates

Description

Compute direct adjusted estimates from a table of statistics.

Usage

```

directly_adjusted_estimates(
  stats_dt,
  stat_col_nms,
  var_col_nms,
  stratum_col_nms = NULL,
  adjust_col_nms = NULL,
  conf_lvls = 0.95,
  conf_methods = "identity",
  weights = NULL
)

```

Arguments

stats_dt	[data.frame] (no default) a data.frame containing estimates and variance estimates of statistics
stat_col_nms	[character] (no default) names of columns in stats_dt containing estimates (statistics); NA statistics values cause also NA confidence intervals

<code>var_col_nms</code>	[character] (default NULL) <ul style="list-style-type: none"> • if NULL, no confidence intervals can (will) be computed • if character vector, names of columns in <code>stats_dt</code> containing variance estimates of the statistics specified in <code>stat_col_nms</code> with one-to-one correspondence; NA elements in <code>var_col_nms</code> cause no confidence intervals to be computed for those statistics; NA variance estimates in <code>stats_dt</code> cause NA confidence intervals; negative values cause an error; Inf values cause <code>c(-Inf, Inf)</code> intervals with confidence interval method "identity", etc.
<code>stratum_col_nms</code>	[NULL, character] (default NULL) names of columns in <code>stats_dt</code> by which statistics are stratified (and they should be stratified by these columns after direct adjusting)
<code>adjust_col_nms</code>	[NULL, character] (default NULL) Names of columns in <code>stats_dt</code> by which statistics are currently stratified and by which the statistics should be adjusted (e.g. "agegroup"). <ul style="list-style-type: none"> • NULL: No adjusting is performed. • character: Adjust by these columns.
<code>conf_lvls</code>	[numeric] (default 0.95) confidence levels for confidence intervals; you may specify each statistic (see <code>stat_col_nms</code>) its own level by supplying a vector of values; values other than between (0, 1) cause an error
<code>conf_methods</code>	[character, list] (default "identity") Method(s) to compute confidence intervals. Either one method for all stats (<code>stat_col_nms</code>) or otherwise this must be of length <code>(length(stat_col_nms))</code> . Each element is passed to <code>[delta_method_confidence_intervals]</code> separately. Can also be "none": This causes no confidence intervals to be calculated for the respective <code>stat_col_nms</code> element(s).
<code>weights</code>	[double, data.table, character] The weights need not sum to one as this is ensured internally. You may supply weights in one of the following ways: <ul style="list-style-type: none"> • double: A vector of weights, the length of which must match the number of strata defined by adjusting variables. • data.table: With one or more columns with names matching to those variables that are used to adjust estimates, and one column named <code>weight</code>. E.g. <code>data.table(agegroup = 1:3, weight = c(100, 500, 400))</code>.

Details

`directadjusting::directly_adjusted_estimates` computes weighted averages and their confidence intervals. Performs the following steps:

- Makes a new `data.table` with data from `stats_dt` without copying any column data to avoid modifying `stats_dt` itself.
- Handles argument `weights` in order to produce a `data.table` of weights if it wasn't one already.
- Inserts the weights into `stats_dt`.

- Weights are merged into `stats_dt` in-place by making a left join on `weights_dt` using `stats_dt` and adding column `weight` resulting from this join into `stats_dt`.
- Re-scale weights to sum to one within each stratum defined by `stratum_col_nms`.
- Computes weighted averages of `stat_col_nms` and `var_col_nms` (the latter with squared weights because they are variances) over `adjust_col_nms`. This results in a `data.table` without column(s) `adjust_col_nms`.
- For each `i` in `seq_along(stat_col_nm)`:
 - If `conf_methods[[i]]` is "none", doesn't compute confidence intervals.
 - Otherwise calls `[delta_method_confidence_intervals]`.
- Sets attribute `directly_adjusted_estimates_meta`. It is a list containing:
 - `call`: The call to `directadjusting::directly_adjusted_estimates`.
 - `stat_col_nms`: The argument as given by the user.
 - `var_col_nms`: The argument as given by the user.
 - `stratum_col_nms`: The argument as given by the user.
 - `adjust_col_nms`: The argument as given by the user.
 - `conf_lvls`: The argument, but always of length `length(stat_col_nms)`.
 - `conf_methods`: The argument, but always of length `length(stat_col_nms)`.
- Returns a `data.table`. Returned columns are those given via `stratum_col_nms`, `stat_col_nms`, and `var_col_nms`.

Value

Returns a `data.table`. Returned columns are those given via `stratum_col_nms`, `stat_col_nms`, and `var_col_nms`.

Examples

```
# directadjusting::directly_adjusted_estimates
library("data.table")
set.seed(1337)

offsets <- rnorm(8, mean = 1000, sd = 100)
baseline <- 100
hrs_by_sex <- rep(1:2, each = 4)
hrs_by_ag <- rep(c(0.75, 0.90, 1.10, 1.25), times = 2)
counts <- rpois(8, baseline * hrs_by_sex * hrs_by_ag)

# raw estimates
my_stats <- data.table::data.table(
  sex = rep(1:2, each = 4),
  ag = rep(1:4, times = 2),
  e = counts / offsets,
  v = counts / (offsets ** 2)
)

# adjusted by age group
my_adj_stats <- directly_adjusted_estimates(
  stats_dt = my_stats,
```

```

    stat_col_nms = "e",
    var_col_nms = "v",
    conf_lvls = 0.95,
    conf_methods = "log",
    stratum_col_nms = "sex",
    adjust_col_nms = "ag",
    weights = c(200, 300, 400, 100)
  )

# adjusted by smaller age groups, stratified by larger age groups
my_stats[, "ag2" := c(1,1, 2,2, 1,1, 2,2)]
my_adj_stats <- directly_adjusted_estimates(
  stats_dt = my_stats,
  stat_col_nms = "e",
  var_col_nms = "v",
  conf_lvls = 0.95,
  conf_methods = "log",
  stratum_col_nms = c("sex", "ag2"),
  adjust_col_nms = "ag",
  weights = c(200, 300, 400, 100)
)

# with no adjusting columns defined you get the same table as input
# but with confidence intervals. this for the sake of
# convenience for programming cases where sometimes you want to adjust,
# sometimes not.
stats_dt_2 <- data.table::data.table(
  sex = 0:1,
  e = 0.0,
  v = 0.1
)
dt_2 <- directadjusting::directly_adjusted_estimates(
  stats_dt = stats_dt_2,
  stat_col_nms = "e",
  var_col_nms = "v",
  conf_lvls = 0.95,
  conf_methods = "identity",
  stratum_col_nms = "sex"
)
stopifnot(
  dt_2[["e"]] == stats_dt_2[["e"]],
  dt_2[["v"]] == stats_dt_2[["v"]],
  dt_2[["sex"]] == stats_dt_2[["sex"]]
)

# sometimes when adjusting rates or counts, there can be strata where the
# statistic is zero. these should be included in your statistics dataset
# if you still want the weighted average be influenced by the zero.
# otherwise you will get the wrong result. sometimes when naively tabulating
# a dataset with e.g. dt[, .N, keyby = "stratum"] one does not get a result
# row for a stratum that does not appear in the dataset even if we know that
# the stratum exists, for instance only the age groups 1-17 are present in
# the dataset.

```

```

stats_dt_3 <- data.table::data.table(
  age_group = 1:18,
  count = 17:0,
  var = 17:0
)

# this goes as intended
dt_3 <- directadjusting::directly_adjusted_estimates(
  stats_dt = stats_dt_3,
  stat_col_nms = "count",
  var_col_nms = "var",
  stratum_col_nms = NULL,
  adjust_col_nms = "age_group",
  weights = data.table::data.table(
    age_group = 1:18,
    weight = 18:1
  )
)

# this does not
dt_4 <- directadjusting::directly_adjusted_estimates(
  stats_dt = stats_dt_3[1:17, ],
  stat_col_nms = "count",
  var_col_nms = "var",
  stratum_col_nms = NULL,
  adjust_col_nms = "age_group",
  weights = data.table::data.table(
    age_group = 1:18,
    weight = 18:1
  )
)

# the weighted average that included the zero is smaller
stopifnot(
  dt_3[["count"]] < dt_4[["count"]]
)

# NAs are allowed and produce in turn NAs silently.
stats_dt_5 <- data.table::data.table(
  age_group = 1:18,
  count = c(NA, 16:0),
  var = c(NA, 16:0)
)
dt_5 <- directadjusting::directly_adjusted_estimates(
  stats_dt = stats_dt_5,
  stat_col_nms = "count",
  var_col_nms = "var",
  adjust_col_nms = "age_group",
  weights = data.table::data.table(
    age_group = 1:18,
    weight = 18:1
  )
)

```

```
stopifnot(
  is.na(dt_5)
)

stats_dt_6 <- data.table::data.table(
  age_group = 1:4,
  survival = c(0.20, 0.40, 0.60, 0.80),
  var = 0.05 ^ 2
)

# you can use conf_method to pass whatever to
# `delta_method_confidence_intervals`.
dt_6 <- directadjusting::directly_adjusted_estimates(
  stats_dt = stats_dt_6,
  stat_col_nms = "survival",
  var_col_nms = "var",
  adjust_col_nms = "age_group",
  weights = data.table::data.table(
    age_group = 1:4,
    weight = 1:4
  ),
  conf_methods = list(
    list(
      g = quote(stats::qnorm(theta)),
      g_inv = quote(stats::pnorm(g))
    )
  )
)
```

Index

confidence_intervals, 2

delta_method_confidence_intervals
 (confidence_intervals), 2

directly_adjusted_estimates, 4